

Cod. 10505

Hose reel machines
Enrolladores



Explorer

Slow reverse double arm gun for high flow

Cañón de riego de impacto de caudal alto



Net weight
Peso neto

11 kg

Connection
Conexión

6 x 130 mm (M8)

Size
Dimensiones

Ø 1812 mm x 595 mm

Nozzle
Boquilla

Ø 22 ÷ 42 mm

Angle
Ángulo

25°

Pressure Presion

Nozzle Boquilla	3 bar		4 bar		5 bar		6 bar		7 bar		8 bar	
	Flow Caudal l/min	Radius Alcance m	Flow Caudal l/min	Radius Alcance m	Flow Caudal l/min	Radius Alcance m	Flow Caudal l/min	Radius Alcance m	Flow Caudal l/min	Radius Alcance m	Flow Caudal l/min	Radius Alcance m
22 mm	522	40	604	44	676	48	741	52	-	-	-	-
24 mm	623	41	720	46	806	50	882	54	-	-	-	-
26 mm	732	43	846	48	946	52,5	1037	56	-	-	-	-
28 mm	848	46	981	50,5	1096	54	1202	58	-	-	-	-
30 mm	974	48	1127	52	1260	56	1381	60	-	-	-	-
32 mm	-	-	1282	54	1433	58	1570	62	1694	66	-	-
34 mm	-	-	-	-	1619	59	1774	64	1913	68	2048	72
36 mm	-	-	-	-	1814	61	1988	66	2144	70	2295	74
38 mm	-	-	-	-	2022	63	2216	68	2390	72	2558	76
40 mm	-	-	-	-	2240	65	2455	69	2648	73	2834	78